



Europäisches
Patentamt

European
Patent Office

Office européen
des brevets



10/043384



Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-
gen stimmen mit der
ursprünglich eingereichten
Fassung der auf dem näch-
sten Blatt bezeichneten
europäischen Patentanmel-
dung überein.

The attached documents
are exact copies of the
European patent application
described on the following
page, as originally filed.

Les documents fixés à
cette attestation sont
conformes à la version
initialement déposée de
la demande de brevet
européen spécifiée à la
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

00203787.7

CERTIFIED COPY OF
PRIORITY DOCUMENT

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

I.L.C. HATTEN-HECKMAN

DEN HAAG, DEN
THE HAGUE,
LA HAYE, LE

18/04/01

THIS PAGE BLANK (USPTO)

THIS PAGE BLANK (USPTO)



Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

**Blatt 2 der Bescheinigung
Sheet 2 of the certificate
Page 2 de l'attestation**

Anmeldung Nr.:
Application no.: 00203787.7
Demande n°:

Anmeldetag:
Date of filing: 31/10/00
Date de dépôt:

Anmelder:
Applicant(s):
Demandeur(s):
Koninklijke Philips Electronics N.V.
5621 BA Eindhoven
NETHERLANDS

Bezeichnung der Erfindung:
Title of the invention:
Titre de l'invention:
Sub-field driven display device and method

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s) revendiquée(s)

Staat:
State:
Pays:

Tag:
Date:
Date:

Aktenzeichen:
File no.
Numéro de dépôt:

Internationale Patentklassifikation:
International Patent classification:
Classification internationale des brevets:

/

Am Anmeldetag benannte Vertragsstaaten:
Contracting states designated at date of filing: AT/BE/CH/CY/DE/DK/ES/FI/FR/GB/GR/IE/IT/LI/LU/MC/NL/PT/SE/TR
Etats contractants désignés lors du dépôt:

Bemerkungen:
Remarks:
Remarques:

THIS PAGE BLANK (USPTO)

Sub-field driven display device and method

EPO - DG 1

31. 10. 2000

(82)

The present invention relates to a sub-field driven display device and method wherein sub-fields are weighted and duplicated for providing a plurality of grey levels by way of a plurality of sub-fields.

5 Such a sub-field driven display and method is known from EP-A-0 896 317 which discloses a colour image display device wherein colour video signals are supplied to red, green and blue light emitting cells, for example the cells of a plasma display device. The device employs the known sub-field method of displaying the required grey scale representation by controlling the light emitting luminous levels of the respective red, green
10 and blue light emitting cells. In this known sub-field method, one display field is divided into a plurality of sub-fields on a time base and light emitting weights are allotted to the respective sub-fields and light emission in each of the respective sub-fields is then either controlled in an on/off manner so as to provide the appropriate grey level gradation. The required gradation is commonly provided by employing a binary ratio weighting for the sub-
15 fields.

Performance can be disadvantageously limited with such known display devices and methods and the present invention seeks to provide for a sub-field driven display device and method offering improved performance. In particular the present invention seeks
20 to provide improved performance through the identification of particular limitations, and related problems, as found in the prior art and which are identified in accordance with the present invention and arise particularly in view of the number of sub-fields employed which serves to disadvantageously limit the performance of known devices and methods due to motion artefacts and the limited number of grey levels available.

25

The present invention further seeks to provide for an improved sub-field driven display device and method which readily allows for the adoption of duplicated sub-field addressing.

According to one aspect of the present invention, there is provided a sub-field driven display device of the type defined above, characterised in that the sub-fields are weighted according to a ternary distribution of sub-field weights.

5 As will be illustrated further within the present application, the adoption of a ternary distribution of weights advantageously optimises the ratio of grey levels to sub-fields adopted such that, when compared with known weighting distributions, and for a given number of sub-fields, the present invention advantageously allows for an increased number of grey levels thereby advantageously enhancing the performance of sub-field driven display
10 devices. Stated in the alternative, the invention therefore has the advantage that, with a minimal number of sub-fields, the highest maximum value of grey level can be achieved while still retaining the possibility of also producing all intermediate grey level values.

The feature defined in claim 2 is particularly advantageous in readily allowing
15 for the application of a duplicated sub-field addressing method which, in turn, advantageously reduces motion artifact problems that can be apparent in such devices.

The feature of claim 3 further facilitates such advantages and the feature defined in claim 4 has the advantage that, with the heaviest weighting value found within the
20 middle of the sub-field weighting distribution, this central sub-field position can advantageously act as a reference time value for motion compensation.

The features defined in claims 5 - 8 relate to corresponding method steps for the present invention and exhibit advantages similar to those discussed above.
25

The feature defined in claim 9 specifically introduces the adoption of a duplicated sub-field addressing method which can readily be achieved in accordance with the sub-field distribution arising in the present invention. Such an addressing method allows for motion artifact reduction, even without use of a motion estimator, and even though the
30 method, if required, can be combined with motion compensation based on motion estimation.

The present invention is described further hereinafter by way of example only, with reference to the accompanying drawings in which:

Fig.1 represents a block diagram of a display device embodying the present invention; and

Fig.2 comprises a tabular representation grey level production for two pixels
5 in accordance with an embodiment of the present invention.

It should be appreciated that the present invention can readily employ the techniques for weighting and distributing duplicated sub fields as disclosed in EP-A-0 899 710, EP-A-0 698 874 and EP-A-0 896 317.

10

As will be appreciated, the present invention relates to the adoption of a ternary weighting distribution for a sub-field driven display device and related method in which, as will be illustrated below, specific advantages leading to an improved performance in display devices can be achieved.

15

For example, the ternary distribution:

1,3,9,27,9,3,1

20

represents a particularly advantageous weighting in accordance with the present invention since the ternary distribution is not only a symmetrical distribution but also offers its maximum value at the centre of the distribution.

25

As will be appreciated, through the effective use of seven sub-fields - each employing a respective one of the weightings noted above - all integer values of grey level between 0 and the maximum possible grey level, 53 in this example, can be realised. When compared, for example, with a binary distribution as known in the prior art, a greater number of sub-fields will be required in order to arrive at a similar number of grey level values. This is particularly true for symmetrical series.

30

The ternary distribution has associated advantages in that it readily allows for particularly effective motion artifact reduction through the application of the known duplicated sub-field addressing method which can, if required, be combined with motion compensation based on motion estimation.

As noted in the above example, it is particularly advantageous to provide for the heaviest weighting value in the centre of the sub-field weighting distribution since this sub-field position can then readily act as a reference time $t=0$, for motion compensation. This can be preferred since the maximum amount of light is generated within the middle of the sub-field distribution and is not liable to be effected by any possible truncation error. The lower weights, i.e. the weighting values of the sub-fields either side of the central heaviest weight, are then effectively duplicated either side of the central weight and turned on in accordance with the example of two driven pixels as illustrated in the accompanying drawing.

Turning now to Fig. 1, there is illustrated in block diagrammatic form one embodiment of a display device 10 according to the present invention. The device 10 includes analogue/digital converters 12, 14, 16 for each of the incoming analogue Red, Green and Blue video signals which converters subsequently deliver the digital video signals to a sub-field converter 18. The signals output from the sub-field converter 18 are received by a sub-field sequence converter 20 including a frame memory which in turn delivers the sub-field divided signal to a display driver 22. The driver 22 is arranged to provide drive signals to the display such as a plasma display panel 24.

Referring now to the drawing, shown in Fig. 2, each of the possible 18 grey levels is identified down the left-hand column whereas the ternary weighting for each of the 5 sub-fields of each of pixels 1 and 2 is illustrated across the top row of the table and confirms that the ternary distribution 1,3,9,3,1 is employed for illustrative purposes within this embodiment of the present invention. The distribution of crosses within the table indicate which of the weighted sub-fields is driven in order to provide the particular grey scale level indicated in the left-hand column.

In further detail, consideration can be given to the distribution of $(2n+1)$ values a_i :

$a_0, a_1, a_2, a_3, \dots, a_{n-1}, a_n, a_{n-1}, \dots, a_3, a_2, a_1, a_0$, while $a_0=1$

With a number of grey levels, G_{2n+1} , equal to (note: consider also the grey value 0):

$$G_{2n+1} = 1 + a_n + 2 \sum_{i=0}^{n-1} a_i$$

5

The symmetrical distribution is constructed in order to apply the distributed sub-field method. The values a_n are integer values, such that all values from 0 to G_{2n+1} can be realised.

10

The heaviest weights will preferably be in the middle of the distribution, while the smaller values are located further away from the middle; therefore $a_0=1$.

A distribution for $n=4$ is advantageously constructed as follows:

15

a_0	a_1	a_2	a_3	a_4	a_3	a_2	a_1	a_0	Construction comment:
1	1	sum 2, so take 3 as next
1	3	3	1	sum 8, so take 9 as next
1	3	9	9	3	1	sum 26, so take 27 as
1	3	9	27	81	27	9	3	1	sum 80, finalise with

Thus all integer values between 0 and a maximum grey level of 161 can be produced giving $G_{2n+1}=162$ grey levels.

20

In general: $a_n = 3^n$, $n=0,1,2,3,\dots$,

Giving: $2n+1$ sub-fields,

While: $G_{2n+1} = 2 \cdot 3^n$.

This provides for a ternary series.

For a symmetrical binary series of $(2n+1)$ sub-fields, with the highest weight in the middle, the number of grey levels equals $G_{2n+1}=2.2^n$, which is a factor $(3/2)^n$ less. At
 5 $(2n+1)=9$ sub-fields (thus $n=4$), this differs a factor 5.0625 (5). This clearly illustrates how, for a given number of sub-fields the device and method of the present invention can provide for an optimum number of grey scale values.

At an even number of sub-fields one additional term is generally to be
 10 determined. To keep the distribution full symmetrical, the heaviest weight can be copied, or repeated, in the middle as follows:

$a_0, a_1, a_2, a_3, \dots, a_{n-1}, a_n, a_n, a_{n-1}, \dots, a_3, a_2, a_1, a_0$, while $a_0=1$

example for $n=3$: 1,3,9,27,27,9,3,1 , $G_8=81$.

15

Alternatively, a series can be developed in which the term a_0 is not duplicated. Using the same values as above this arrives at:

1,2,6,18,54,18,6,2

20

which for the same number of eight sub-fields gives 108 grey levels.

As will be appreciated, the maximum possible number of grey levels is advantageously achieved in accordance with the present invention while, if required, for the
 25 highest of all possible weights, a symmetrical value can also be adopted. When also applying the duplicate sub-field method so as to achieve motion compensation, the pixels identified as A pixel and B pixel in the duplicated sub-field method can advantageously be addressed by one of the symmetrical options.

It should of course be appreciated that the present invention can be used in all
 30 displays which employ sub-field distributions and which include, but are not limited to, Plasma Display Panels, Digital Mirror Devices and Dynamic Foil Displays.

Also the invention is not restricted to the details of the foregoing embodiment since, for example an asymmetrical ternary distribution, and without having the highest weighted value centrally located, could still nevertheless advantageously be employed so as

5 to arrive at advantages offered by the present invention.

THIS PAGE BLANK (USPTO)

CLAIMS:

EPO - DG 1

31. 10. 2000

(82)

1. A sub-field driven display device (10) having a sub-field converter (18) for converting video signals into sub-field data in which the sub-fields are weighted and duplicated for achieving a plurality of grey levels by way of a plurality of sub-fields, characterised in that the sub-field converter (18) is arranged to weight the sub-fields as a ternary distribution of sub-field weights.
2. A display device (10) as defined in claim 1, wherein the sub-field converter (18) is arranged to employ symmetrical duplicated ternary weights.
3. A display device (10) as defined in claim 1 or 2, wherein the sub-field converter (18) is arranged to distribute the ternary weights in a manner of increasing weighted value toward a central value or values.
4. A display device (10) as defined in claims 1, 2 or 3, wherein sub-field converter (18) is arranged to provide the highest sub-field weight at the centre of the ternary distribution.
5. A display device (10) as defined in any one of claims 1 - 4, and including motion compensation means employing motion estimation serving to enhance motion artefact reduction.
6. A display device (10) as defined in any one of claims 1 - 5, wherein the sub-field converter (18) is arranged to alternate light output control patterns in predetermined units of the display.
7. A display device (10) as defined in claim 6, wherein the pattern comprises a checker-board pattern.

8. A method of driving a display device (10) by means of a plurality of weighted and duplicated sub-fields, characterised by the step of weighting the sub-field according to a ternary distribution of weights.

5 9. A method as defined in claim 8, and employing symmetrical duplicated ternary weights.

10. A method as defined in claim 8 or 9, wherein the ternary weights are distributed in a manner of increasing weighted value toward a central value or values.

10

11. A method as defined in any one of claims 8, 9, or 10, wherein the highest sub-field weight is found in the centre of the ternary distribution.

12. A method as defined in any one of claims 5 - 11 and including the step of duplicated sub-field addressing.

15

13. A method as defined in claim 12, and including motion compensation employing motion estimation serving to enhance motion artefact reduction.

20 14. A method as defined in claim 12 or 13, and including the step of alternating light output control patterns in predetermined units of the display.

15. A method as defined in claim 14, wherein the pattern comprises a checker board pattern.

10

25.10.2000

EPO - DG 1

ABSTRACT:

31. 10. 2000

(82)

The present invention provides for a sub-field driven display device and related method wherein sub-fields are weighted and duplicated for achieving a plurality of grey levels by way of a plurality of sub-fields, and in which the sub-fields are weighted as a ternary distribution of sub-field weights.

5

Fig.1

THIS PAGE BLANK (USPTO)

PHNL000547

EPO - DG 1

31. 10. 2000

(82)

1/2




FIG. 1

PHNL000547

2/2

		Pixel 1						Pixel 2					
			1	3	9	3	1		1	3	9	3	1
0	s												
1	d		x										x
2	s		x				x		x				x
3	d			x								x	
4	d		x			x				x			x
5	d		x	x			x		x			x	x
6	s			x		x				x		x	
7	d		x	x		x				x		x	x
8	s		x	x		x	x		x	x		x	x
9	s				x						x		
10	d		x		x						x		x
11	s		x		x		x		x		x		x
12	d			x	x						x	x	
13	d		x		x	x				x	x		x
14	d		x	x	x		x		x		x	x	x
15	s			x	x	x				x	x	x	
16	d		x	x	x	x				x	x	x	x
17	s		x	x	x	x	x		x	x	x	x	x

FIG. 2